

# Dell Smart-UPS DLT3000RM2UC

## Technical Specifications

### Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery Mounting	Stand alone battery stack
Expected Battery Life (years)	3-5
RBC Quantity	1
Battery blocks per string	--

### Physical

Maximum Height	3.4 inches (8.6 cm)
Maximum Width	17.0 inches (43.2 cm)
Maximum Depth	26.9 inches (68.3 cm)
Rack Height	2U
Net Weight	97.6 lbs. (44.28 kg)
Shipping weight	114.0 lbs. (51.7 kg)
Shipping Height	10.0 inches (25.4 cm)
Shipping Width	38.6 inches (98 cm)
Shipping Depth	23.7 inches (60.1 cm)
Color	Black
Units per Pallet	8.0

### Environmental

Operating Temperature	32 - 104 °F ( 0 - 40 °C )
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000ft ( 0-3000meters )
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000ft ( 0-15000meters )

### Conformance

Approvals	OSHPD, cULus, ENERGY STAR V2.0
Standard Warranty	3 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs