

Dell Smart-UPS DLT1500RM3UC

technical specifications

UPS Model	DLTL1500RM3UC
Output	
Output power capacity	1350 Watts / 1500 VA
Nominal output voltage	120V
Output voltage distortion	Less than 5% at full load
Output frequency (sync to mains)	50/60 Hz +/- 3 Hz (auto sensing)
Waveform type	Sine Wave
Output connections	(6) NEMA 5-15R
Switched outlet group	Yes/One
Efficiency at full load	>96%
Input	
Nominal input voltage	120V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input connections	NEMA 5-15P
Input voltage range for main operations	82 – 144Vac
Batteries and runtime	
Battery type	Lithium-ion
Runtime (Full load/ Half load)	5 / 12.6 min
Communications and management	
Interface port(s)	Serial (RJ45), SmartSlot, USB, APC SmartConnect (RJ45)
SmartSlot™ interface availability	Yes. (AP9641 is pre-installed in -NC models)
Control panel	Multi-function LCD status and control console
Physical	
Net HxWxD	5.14" x 17.25" x 12"
Rack height	3U
Net weight	43 lbs
Shipping weight	50 lbs
Shipping HxWxD	11" x 17.64" x 23"
Color	Black [Silver front bezel]
Environmental	
Operating environment	32 – 104 °F (0 – 40 °C)
Operating relative humidity	0 – 95%
Operating elevation	0-10000 feet (0-3000 meters)
Storage temperature	5 – 113 °F (-15 – 45 °C) short term storage
Storage relative humidity	0 – 95%, non-condensing
Storage elevation	0-25000 feet (0-7620 meters)
Audible noise at 1 meter from surface of unit	< 45.0dBA
Conformance	
Regulatory approvals	UL 1778, UL 1973, CSA
Standard warranty	5-Year UPS and batteries